

Product Description & Application

The DuPont™ Tyvek® Nail Sealing Tape is a high quality, single-sided polyethylene foam tape. It is, designed especially for the sealing of nail or screw holes and staples between counter battens and Tyvek® underlays. It adheres to all Tyvek® underlays and on PP nonwovens and coated sheets. Tyvek® Nail Sealing Tape is recommended wherever an improved rain resistance in pitched roofs is required.

Specifications

PROPERTY	VALUE
Stylename	1310N
Colour	Black
Thickness	4 mm
Volume weight	30 kg/m ³
Temperature range	-30 °C to 100 °C
Processing temperature	>0 °C

Use and Care Recommendations

- DuPont™ Tyvek® Nail Sealing Tape may be applied either directly onto the counter batten, before it is installed, or on Tyvek® underlay.
- In any case, care should be taken to ensure enough contact pressure over the length of the counter batten to the underlying Tyvek® underlay.
- The surface must be dry and free from frost, dust, oil and grease before applying Tyvek® Nail Sealing Tape.
- May be stored in unopened original packaging for 24 months, away from direct sunlight, in a cool, dry, frost-free place at temperatures between 5 °C to 25 °C.

Date: January 15, 2014

DuPont de Nemours (Luxembourg) S.à r.l.
Rue General Patton, L - 2984 Luxembourg
Tel.: +352 3666 5885

tyvek.info@lux.dupont.com

www.construction.tyvek.com

This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.

